



COMMUNICATIONS PROCESSOR CP 1243-1 FOR CONNECTING SIMATIC S7-1200 TO TELECONTROL SERVER BASIC VIA ETHERNET ALSO SUITED FOR SAFE COMMUNICATION WITH NETWORK WITH FIREWALL AND VPN

Transmission rate

Transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet for power supply 	1 0
Type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Consumed current	
<ul style="list-style-type: none"> from backplane bus / for DC / at 5 V / typical 	0.25 A
Active power loss	1.25 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation for horizontally arranged busbars / during operation during storage during transport 	-20 ... +60 °C -20 ... +70 °C -40 ... +70 °C -40 ... +70 °C

Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	110 mm
Depth	75 mm
Net weight	0.122 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Product properties, functions, components / general

Number of units	
• per CPU / maximum	3

Performance data / S7 communication

Number of possible connections / for S7 communication	
• Note	like CPU

Performance data / telecontrol

Suitability for use	
• Node station	No
• substation	Yes
• TIM control center	No
Control center connection	to be used with Telecontrol Server Basic
Control center connection / by means of a permanent connection	supported
Control center connection / Note	Connection to Scada system via Telecontrol Server Basic
Protocol / is supported	
• DNP3	No
• IEC 60870-5	No
Product function / data buffering if connection is aborted	Yes
• Note	64,000 values
Number of data points per station / maximum	200

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
• program download with SIMATIC STEP 7	Yes
• Remote firmware update	Yes

Product functions / management, configuration

Configuration software

- required

STEP 7 Basic/Professional V13 Update 2 + HSP (TIA Portal) or higher

Product functions / Security

Firewall version

stateful inspection

Product function / with VPN connection

IPSec

Type of encryption algorithms / with VPN connection

AES-256, AES-192, AES-128, 3DES-168

Type of authentication procedure / with VPN connection

Preshared key (PSK), X.509v3 certificates

Type of hashing algorithms / with VPN connection

MD5, SHA-1

Number of possible connections / with VPN connection

8

Product function

- password protection for Web applications
- password protection for teleservice access
- encrypted data transmission
- ACL - IP-based
- ACL - IP-based for PLC/routing
- switch-off of non-required services
- Blocking of communication via physical ports
- log file for unauthorized access

No

No

Yes

No

No

Yes

No

No

Product functions / Time

Protocol / is supported / NTP

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

12.03.2015