

SIMATIC HMI KP8 PN Key Panel, 8 short-stroke switches with multi-colored LEDs, PROFINET interfaces 8 configurable DI/DO pins, 24 V DC can be looped through parameterizable as of STEP 7 V5.5



General information	
Product type designation	KP8 PN
Control elements	
With parameterizable keys	Yes
Keyboard fonts	
<ul style="list-style-type: none"> • Membrane keyboard <ul style="list-style-type: none"> — user-definable label membrane keys • Function keys <ul style="list-style-type: none"> — Number of function keys • Short-stroke keys <ul style="list-style-type: none"> — Number of short-stroke keys 	Yes 8 8
Expansions for operator control of the process	
<ul style="list-style-type: none"> • DP direct LEDs (LEDs as S7 output I/O) • Number of color modes for LED • Direct keys (keys as S7 input I/O) 	8; Adjustable brightness 5; red, green, blue, yellow, white 8
Installation type/mounting	
Mounting type	Mounting clip
Mounting position	vertical

Rack mounting	No
Front mounting	Yes; Compatible with Extension Units dimensions
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Number of slots for command devices and signaling units	0

Supply voltage

Type of supply voltage	DC
Rated value (DC)	24 V; 24 V can be looped through connector, interrupted when pulled
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption (rated value)	0.3 A
-----------------------------------	-------

Type of output

LED colors	
• red	Yes
• yellow	Yes
• green	Yes
• white	Yes
• blue	Yes

Digital inputs

Number of digital inputs	8; Total inputs and outputs max. 8 and 1x SIL 2 or 2x SIL 3
--------------------------	---

Input voltage

• Rated value (DC)	24 V
--------------------	------

Digital outputs

Number of digital outputs	8; Max. 8 inputs and outputs (total)
---------------------------	--------------------------------------

Short-circuit protection	Yes
--------------------------	-----

Switching capacity of the outputs

• with resistive load, max.	100 mA
-----------------------------	--------

Output voltage

• Rated value (DC)	24 V; Non-isolated
--------------------	--------------------

Total current of the outputs

• Current per channel, max.	100 mA
• Current per group, max.	800 mA

Interfaces

Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
--	--

Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	
• Number of ports of the integrated switch	2; Per port
Protocols	
PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
PROFIsafe	No
PROFIBUS	No
MPI	No
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
• TCP/IP	No
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
• AS-Interface Safety at Work	No
• CAN	No
• Data-Highway	No
• DeviceNet	No
• DeviceNet Safety	No
• EtherNet/IP	No
• Foundation Fieldbus	No
• INTERBUS	No
• INTERBUS-Safety	No
• Local Operating Network	No
• MODBUS	No
• SafetyBUS p	No
• SERCOS	No
• SUCOnet	No
• other bus systems	No
Test commissioning functions	
Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; Group 1, measured at a distance of 10 m
• Limit class B, for use in residential areas	No

Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
<ul style="list-style-type: none"> • Enclosure Type 4 at the front • Enclosure Type 4x at the front 	<p>No</p> <p>Yes; Incl. NEMA12</p>
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
KC approval	Yes
Suitable for safety functions	Yes
Use in hazardous areas	
<ul style="list-style-type: none"> • ATEX Zone 2 • ATEX Zone 22 • cULus Class I Zone 1 • cULus Class I Zone 2, Division 2 • FM Class I Division 2 	<p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes</p> <p>Yes</p>
Marine approval	
<ul style="list-style-type: none"> • Germanischer Lloyd (GL) • American Bureau of Shipping (ABS) • Bureau Veritas (BV) • Det Norske Veritas (DNV) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (Class NK) • Polski Rejestr Statkow (PRS) 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • max. • Operation (vertical installation) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. • Operation (max. tilt angle) <ul style="list-style-type: none"> — At maximum tilt angle, min. — At maximum tilt angle, min. • Operation (vertical installation, portrait format) <ul style="list-style-type: none"> — For vertical installation, min. — For vertical installation, max. • Operation (max. tilt angle, portrait format) <ul style="list-style-type: none"> — At maximum tilt angle, min. — At maximum tilt angle, min. 	<p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>45 °C</p> <p>0 °C</p> <p>55 °C</p> <p>0 °C</p> <p>45 °C</p>

Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
Configuration	
Configuration software	
• STEP 7 Basic (TIA Portal)	Yes
• STEP 7 Professional (TIA Portal)	Yes
Functionality under WinCC (TIA Portal)	
Process coupling	
• S7-1200	Yes; with ET 200pro CPU and ET 200S CPU
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes; with F-CPU: STEP 7 V11 SP1 (or higher) and Safety V11 (or higher) or SIMATIC STEP 7 Basic V11 (or higher)
• LOGO!	No
• WinAC	Yes
• SINUMERIK	No
• SIMOTION	No
• Allen Bradley (EtherNet/IP)	No
• Allen Bradley (DF1)	No
• Mitsubishi (MC TCP/IP)	No
• Mitsubishi (FX)	No
• OMRON (FINS TCP)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus TCP/IP)	No
• Modicon (Modbus)	No
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
• Aluminum	No
• Stainless steel	No
Service life	
• Short-stroke keys (in switching cycles)	1 500 000
• LEDs (ON period)	100 %
Dimensions	
Width of the housing front	98 mm
Height of housing front	155 mm
Mounting cutout, width	68 mm; Max. thickness of mounting plate 2 - 6 mm

Mounting cutout, height	129 mm
Overall depth	49 mm; Incl. angled SIMATIC Ethernet connector
Weights	
Weight without packaging	280 g
last modified:	12/10/2020