



❗ Discontinued

Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 1 at 15 VA Class 3 at 18 VA Class 0.5 at 10.5 VA
[In] rated current	400 A

Complementary

Current transformer type	Tropicalised for busbar and cable
Current transformer ratio	400/5
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
Mounting mode	Insulated locking screw
Mounting support	DIN rail Mounting plate Busbar
Width	56 mm outside:
Height	88.5 mm outside:
Depth	60 mm outside:
Diameter	22 mm
Net weight	0.27 kg
Cable outer diameter	22 mm - cable 0... 150 mm ²
Opening of bars	30 x 10

Environment

Standards	IEC 60044-1 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	95... 100 %

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

Packing Units

Package 1 Weight	0.342 kg
Package 1 Height	0.710 dm
Package 1 width	0.680 dm
Package 1 Length	0.920 dm

Contractual warranty

Warranty	18 months
----------	-----------