

PRODUCT DATASHEET

SMART+ WIFI FLOOD 50 W

SMART+ DIMMABLE | Floodlights with WiFi technology



Areas of application

- Building facades

Product benefits

- Easy and quick installation
- Semi-frosted, tempered glass cover for uniform illumination

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Network protocol: WiFi
- Mounting bracket for up to 180° tilting
- Type of protection: IP65
- Connection via 0.5 m cable, wiring required



TECHNICAL DATA

Electrical data

Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.90
Operating mode	Mains voltage


Photometrical data

Light color (designation)	Warm White
Standard deviation of color matching	< 6 sdcn
Nominal luminous flux	4250 lm
Luminous flux	4250 lm
Luminous efficacy	85 lm/W
Color temperature	3000 K
Color rendering index Ra	≥ 80

Light technical data

Beam angle	100 °
Starting time	< 0.5 s

Dimensions & Weight



Product weight	1000.00 g
Length	237.00 mm
Width	200.00 mm
Width (incl. round luminaires)	200.00 mm
Height	36.00 mm
Height (incl. round luminaires)	36.00 mm

Lifespan

Number of switching cycles	30000
----------------------------	-------

Colors & materials

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Glass

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Mounting location	Wall

Capabilities

Dimmable	Yes
Type of connection	Cable, 3-pole
Compatible smart home technology	Google Assistant / Amazon Alexa
LED module replaceable	Not replaceable

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Protection class	I
Type of protection	IP65

Energy labelling regulation data acc EU 2019/2015

Correlated colour temperature type	SINGLE_VALUE
------------------------------------	--------------

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

DOWNLOAD DATA



User instruction
SMART WIFI FLOOD



Declarations of conformity
SMART OUTD WIFI FLOOD DG

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075474666	Folding box 1	234 mm x 54 mm x 249 mm	1105.00 g	3.15 dm ³
4058075474673	Shipping box 8	487 mm x 237 mm x 273 mm	9416.00 g	31.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.