

# PRODUCT DATASHEET UVC LED DISINFECTION BOX BATTERY UVC LED

UVC LED DISINFECTION BOX | Portable disinfection unit, recharchable via USB



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	5.00 W
Nominal voltage	5 V
Nominal current	1000 mA
Power factor $\lambda$	> 0.90
Protection class	Ш
Operating mode	Battery

## Photometrical data

Luminous efficacy	lm/W
Beam angle	120 °

# **Dimensions & Weight**



Length	219.00 mm
Width	126.00 mm
Height	63.00 mm
Product weight	450.00 g
Cable length	1000 mm

# Materials & Colors

Product color	White	
Housing color	White	
Body material	Acrylonitrile butadiene styrene (ABS)	
Mercury content	0.0 mg	

# Application & Mounting

Ambient temperature range	-10+40 °C
Temperature range at storage	-20+80 °C
Type of connection	USB
Type of protection	IP20
Dimmable	No
Mounting type	Standing
Mounting location	All surfaces

#### Lifespan

Lifespan L70/B50 at 25 °C	1000 h
Number of switching cycles	30000

# Emergency lighting

Battery charging time	1 h

## DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction BATTERY UVC LED DISINFECTION BOX
1	Tender documents Tender Text 4058075515994
	M4D file (3D Model with rotation axis) UVC Disinfection Box - 3D-Model - 3DSMAX
	M4D file (3D Model with rotation axis) UVC Disinfection Box - 3D-Model - FBX

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075515994	Folding box 1	78 mm x 238 mm x 155 mm	553.00 g	2.88 dm <sup>3</sup>
4058075516007	Shipping box 6	327 mm x 247 mm x 260 mm	3654.00 g	21.00 dm <sup>3</sup>
4058075564398	Shipping box 6	327 mm x 247 mm x 260 mm	3654.00 g	21.00 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.