Product data sheet Characteristics

ETK12312

Ultra - minitrunking - 12 x 12 mm - PVC - white - 2 m





Main

		ā
Product or component type	Mini trunking	
Colour tint	White RAL 9010	1
Quantity per set	224 m	

Complementary

o o i i pio i i o i i cai y		Ti de la companya de
Trunking material	Plastic	
Compartment partitioning	1 compartment	
Trunking dimension	12 x 12 mm	
Fixing mode	Power cable : screw-fixed Pre-punched fixing hole with distance of 230 mm between centers	- ciriim
Material	PVC (polyvinyl chloride)	
Length	2000 mm	
Height	12 mm	<u>v</u>
Width	12 mm	-

Environment

IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-560 °C
Environmental health and issues	Cadmium free Lead free
Product certifications	Low voltage directive 2006/95/EC
Standards	EN 50085-1 : 2005 EN 50085-2-1 : 2006

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1139 - Schneider Electric declaration of conformity	2

	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Need no specific recycling operations
Contractual warranty	
Warranty period	18 months