## Product data sheet Characteristics

# ETK25316

Ultra - mini trunking - 25 x 16 mm - PVC - white - 2 m





#### Main

Mani		
Product or component type	Mini trunking	
Device application	Cable distribution	
Colour tint	White RAL 9010	
Quantity per set	104 m	

### Complementary

Trunking material	Plastic	
Compartment partitioning	1 compartment	
Trunking dimension	25 x 16 mm	
Fixing mode	Power cable : screw-fixed Pre-punched fixing hole with distance of 230 mm between centers	
Material	PVC (polyvinyl chloride)	<u>,                                    </u>
Length	2000 mm	
Height	25 mm	
Width	16 mm	? ?. {

#### Environment

IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-560 °C
Environmental health and issues	Cadmium free Lead free
Standards	EN 50085-1 : 2005 EN 50085-2-1 : 2006

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1139 - Schneider Electric declaration of conformity	

## Schneider Electric declaration of conformity

REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Need no specific recycling operations