



Main

Range	Rilux
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Maintained
Colour	White
Light source	Fluorescent tube x 8 W G5
Light source colour	White
Cover type	Transparent
Number of batteries	1 x 6 V 0.6 Ah Ni-Cd (Nickel-Cadmium)
Wiring device additional information	Can be inhibited with rest mode via Teleur range of remote controls

Complementary

[Ue] rated operational voltage	200...230 V AC/DC at 50 Hz
Power consumption in VA	10.1 VA
Current consumption	43 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	24 h
Luminous flux	Emergency condition : 75 lm Maintained mode : 90 lm
Material	Housing : plastic Cover : plastic
Device mounting	Flush Surface ceiling Surface wall
Height	100 mm
Width	331 mm

Depth	46 mm
Product weight	0.65 kg
Market segment	Small commercial

Environment

IP degree of protection	IP42
IK degree of protection	IK06
Ambient air temperature for operation	0...40 °C
Fire resistance	850 °C
Standards	EN 60598-2-22 IEC 50-11 IEC 695-2-1 EN 60695-2-10

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0833 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product Environmental Profile
Product end of life instructions	Available End of Life Information

Contractual warranty

Warranty period	18 months
-----------------	-----------