

# **PRODUCT DATASHEET** HQI-E 70 W/NDL CL

POWERSTAR HQI-E clear | Metal halide lamps for open and enclosed luminaires



## **AREAS OF APPLICATION**

- Shopping arcades
- Conference rooms, auditoriums, libraries
- Factories and workshops
- Exhibition halls and trade fairs
- Pedestrian zones, public squares
- Outdoor applications only in suitable luminaires

## **PRODUCT BENEFITS**

- E27 screw base for simple lamp handling
- Different light colors

#### **BENEFITS OF OSRAM UV FILTER TECHNOLOGY**

- Reduced material stress within the luminaire
- $\,$  The UV filter on the lamp complies with the requirements of IEC 61167



# **TECHNICAL DATA**

## Electrical data


Rated wattage	70.00 W
Lamp current	1.0 A
PFC capacitor at 50 Hz	12 μF <sup>1)</sup>
Nominal wattage	70.00 W
Ignition voltage	3.6 / 5.0 kVp <sup>2)</sup>

 $<sup>^{1)}</sup>$  At rated voltage and cos  $\phi \geq 0.9$ 

#### Photometrical data

Rated lamp efficacy (standard condition)	79 lm/W
Rated luminous flux	5500 lm
Color temperature	4500 K
Light color	4500
Rated LLMF at 2,000 h	0.84
Rated LLMF at 4,000 h	0.76
Rated LLMF at 6,000 h	0.69
UV protection	Yes
Luminous flux	5500 lm
Color rendering index Ra	77

# Dimensions & weight





E27 IEC 7004-21

Diameter	55.0 mm
Length	144.0 mm
Light center length (LCL)	89.0 mm
Product weight	71.15 g

# Temperatures & operating conditions

Maximum permitted outer bulb temperature	330 °C
--	--------

<sup>2)</sup> Minimum / Maximum

Maximum permitted base edge temperature	210 °C

## Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.95
Rated lamp survival factor at 6,000 h	0.50
Lifespan B50	6000 h

## Additional product data

Base (standard designation)	E27
Design / version	Clear
Mercury content	8.0 mg

## Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	No

#### Certificates & standards

Energy efficiency class	A
Energy consumption	77 kWh/1000h

#### Country-specific categorizations

	CS/UB-70/842-H/E/SL-E27-56/141
--	--------------------------------

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300397825	HQI-E 70 W/NDL CL	Shipping carton box 20	355 mm x 186 mm x 294 mm	19.41 dm³	2458.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.